

## 25000 20000 Typical DAM, -40 F 15000 Stress - PSI Typical DAM, 75 F Typical DAM, 150 F Typical DAM, 225 F 10000 5000 0 0.005 0.01 0.015 0.02 0.025 0 0.03 0.035 Strain - in./in.

## VLF 80107 CC Tensile Stress/Strain (Molded Specimen Data)

No information supplied by RTP Company constitutes a warranty regarding product performance or use. Any information regarding performance or use is only offered as suggestion for investigation for use, based upon RTP Company or other customer experience. RTP Company makes no warranties, expressed or implied, concerning the suitability or fitness of any of its products for any particular purpose. It is the responsibility of the customer to determine that the product is safe, lawful and technically suitable for the intended use. The disclosure of information herein is not a license to operate under, or a recommendation to infringe any patents.



## 18000 16000 14000 12000 Stress - PSI 10000 8000 6000 Molded Tensile Bars Approximate Longitudinal Orientation Behavior 4000 Approximate Transverse Orientation Behavior 2000 0 0 0.005 0.01 0.015 0.02 0.025 0.03 Strain - in./in.

## VLF 80107 CC Design Data (75 Degrees F)

No information supplied by RTP Company constitutes a warranty regarding product performance or use. Any information regarding performance or use is only offered as suggestion for investigation for use, based upon RTP Company or other customer experience. RTP Company makes no warranties, expressed or implied, concerning the suitability or fitness of any of its products for any particular purpose. It is the responsibility of the customer to determine that the product is safe, lawful and technically suitable for the intended use. The disclosure of information herein is not a license to operate under, or a recommendation to infringe any patents.